



Stainless Steel Industrial Cleaning Technology

Series X81

**Automatic parts washer with hot water and
bio-degradable detergent
Low water level shut-off included**

**L35/08
L55/08**



L90/08

For medium/small applications

		L35/08	L55/08	L90/08
Basket diameter	mm	380	600	780
Load height	mm	340	340	500
Tank capacity	lt.	40	80	85
Spray pressure	bar	2.5	2.4	2.4
Spray rate	l/min	65	70	90
Pump	hp	0.75	0.75	1
Water heater	KW	2	3	4
Power requirements	KW	2.55	3.55	4.75
Temperature	°C	0°-60°	0°-60°	0°-60°
Voltage	V	230	230-230/400	230/400
Fases	Ph	1	1/3	3
Load weight	Kg	70	100	150
Timer	min	0-60	0-60	0-60
Cleaning temperature	C	0-60	0-60	0-60
Width	mm	750	880	1075
Depth (lid open)	mm	680	880	1190
Height (lid open)	mm	1360	1630	1740
Shipping dimensions WxDxH	mm	750x550x1050	900x700x1020	1150x920x1250
Dry weight	Kg	50	60	80

We reserve the right to modify without notice

OPTIONAL

Insulation > 60°C

Electro fan for steam outlet

Tank refilling

Oil skimmer (no L35)

Stainless steel pipes and basket

Drain pump (except for L35)

Motorised basket (except for L35)



D-Grease (UK) Ltd
 Unit 3, North Gawber Ind Est.
 Blacker Road, Mapplewell
 Barnsley S75 6BS
 Tel: 01226 230890 Fax: 01226 381100